

# NATURAL GAS ENGINE OILS

- **NG LUBE Series**

## TYPICAL CHARACTERISTIC

## KARAKTERISTIK TIPIKAL

Typical Characteristics	ASTM Method	Test Result Typical
		Low Ash
		SAE 40
Viscosity Kinematic at 40 °C, cST	D-445	120.60
at 100 °C, cST	D-445	14.46
Viscosity Index	D-2270	121
Specific Gravity at 15/4°C	D-1298	0.8755
Colour ASTM	D-1500	L5.0
Total Base Number (TBN) (mg KOH/g)	D-2896	4.64
Sulphated Ash, %wt	D-874	0.53

## NG LUBE LONG LIFE □ MINYAK LUMAS MESIN BERBAHAN BAKAR GAS KUALITAS PREMIUM NG LUBE □ MINYAK LUMAS MESIN GAS

## TYPICAL CHARACTERISTIC

## KARAKTERISTIK TIPIKAL

No.	Typical Characteristics	ASTM Method	NG LUBE	
			30	40
1	No. SAE		30	40
2	Density at 15 °C (kg/L)	D-4052	0.8876	0.8917
3	Viscosity Kinematic at 40 °C, cST	D-445	93.37	139.90
		at 100 °C, cST	D-445	11.05
4	Viscosity Index	D-2270	103	99
5	Colour ASTM	D-1500	L5.0	L5.5
6	Flash Point (°C)	D-92	237	249
7	Total Base Number (mg KOH/g)	D-2896	5.52	5.52
8	Sulphated Ash (%wt)	D-874	0.41	0.41
9	Calcium Content (%wt)	AAS	0.132	0.132